

# Summary of product characteristics for a biocidal product

**Product name:** Aquawood TIG, in different shades, Part I, see attached list.

**Product type(s):** PT08 - Wood preservatives (Preservatives)

**Authorisation number:**

**R4BP 3 asset reference number:** RO-0009884-0000

## Table Of Contents

Administrative information	1
1.1. Trade names of the product	1
1.2. Authorisation holder	1
1.3. Manufacturer(s) of the biocidal products	1
1.4. Manufacturer(s) of the active substance(s)	1
2. Product composition and formulation	2
2.1. Qualitative and quantitative information on the composition of the biocidal product	2
2.2. Type of formulation	3
3. Hazard and precautionary statements	3
4. Authorised use(s)	3
4.1.1 Use-specific instructions for use	4
4.1.2 Use-specific risk mitigation measures	4
4.1.3 Where specific to the use, the particulars of likely direct or indirect effects, first aid	4
4.1.4 Where specific to the use, the instructions for safe disposal of the product and its	4
4.1.5 Where specific to the use, the conditions of storage and shelf-life of the product under	4
5. General directions for use	5
5.1. Instructions for use	5
5.2. Risk mitigation measures	5
5.3. Particulars of likely direct or indirect effects, first aid instructions and emergency measures to	5
5.4. Instructions for safe disposal of the product and its packaging	5
5.5. Conditions of storage and shelf-life of the product under normal conditions of storage	5
6. Other information	5

## Administrative information

### 1.1. Trade names of the product

Aquawood TIG, in different shades, Part I, see attached list.

### 1.2. Authorisation holder

<b>Name and address of the authorisation holder</b>	Name	ADLER-Werk Lackfabrik Johann Berghofer GmbH & Co KG
	Address	Bergwerkstraße 22 6130 Schwaz Austria
<b>Authorisation number</b>		
<b>R4BP 3 asset reference number</b>	RO-0009884-0000	
<b>Date of the authorisation</b>	22/01/2013	
<b>Expiry date of the authorisation</b>	31/03/2020	

### 1.3. Manufacturer(s) of the biocidal products

<b>Name of the manufacturer</b>	Adler-Werk Lackfabrik Johann Berghofer GmbH & Co KG
<b>Address of the manufacturer</b>	Bergwerkstraße 22 6130 Schwaz Austria
<b>Location of manufacturing sites</b>	Bergwerkstraße 22 6130 Schwaz Austria

### 1.4. Manufacturer(s) of the active substance(s)

<b>Active substance</b>	39 - 3-iodo-2-propynylbutylcarbamate (IPBC)
<b>Name of the manufacturer</b>	Troy Corporation
<b>Address of the manufacturer</b>	Wunstorfer Straße 40 30926 Seelze Germany
<b>Location of manufacturing sites</b>	8 Vreeland Road 1111 Florham Park, NJ United States

<b>Active substance</b>	39 - 3-iodo-2-propynylbutylcarbamate (IPBC)
<b>Name of the manufacturer</b>	LANXESS Deutschland GmbH
<b>Address of the manufacturer</b>	CHEMPARK Leverkusen 51369 Leverkusen Germany
<b>Location of manufacturing sites</b>	CHEMPARK Leverkusen 51369 Leverkusen Germany

<b>Active substance</b>	51 - tebuconazole
<b>Name of the manufacturer</b>	LANXESS Deutschland GmbH
<b>Address of the manufacturer</b>	CHEMPARK Leverkusen 51369 Leverkusen Germany
<b>Location of manufacturing sites</b>	CHEMPARK Leverkusen 51369 Leverkusen Germany

## 2. Product composition and formulation

### 2.1. Qualitative and quantitative information on the composition of the biocidal product

Common name	IUPAC name	Function	CAS number	EC number	Content (%)
3-iodo-2-propynylbutylcarbamate (IPBC)	3-iodo-2-propynyl butylcarbamate	Active Substance	55406-53-6	259-627-5	0.8
tebuconazole	1-(4-chlorophenyl)-4,4-dimethyl-3-(1,2,4-triazol-1-ylmethyl)pentan-3-ol	Active Substance	107534-96-3	403-640-2	0.4
Confidential non-active substances					98.8

## 2.2. Type of formulation

AL - Any other liquid

## 3. Hazard and precautionary statements

### Hazard statements

Contains IPBC. May produce an allergic reaction.

### Precautionary statements

## 4. Authorised use(s)

### 4.1 Use description

#### Use 1 - Wood preservative

### Product type

PT08 - Wood preservatives (Preservatives)

### Where relevant, an exact description of the authorised use

Target harmful organisms: I.1.1.1 Wood staining fungi I.1.1.3 Wood rotting fungi  
Development stage of target organisms: II.1 Not applicable  
Function/mode of action: III.2 Preventive  
Field of use: IV.1 Use category 2 IV.2 Use category 3  
Application aim: VII.1 Preventative against wood staining fungi VII.2 Preventative against wood rotting fungi  
User category: V.1 Professional V.2 Industrial  
Application method: V1.2 Professional – Manual dipping V1.2.1 Industrial – Flow coating (deluge) or manual dipping  
Manner and area of use: Authorisation is granted for Use Class 2 and Use Class 3.

### Target organism(s) (including development stage)

Wood disfiguring fungi-  
Wood rotting fungi-

### Field(s) of use

Indoor  
Outdoor

### Application method(s)

Open system: dip treatment -  
Manuel dipping by professionals or industry.

	Open system: deluging - Flow coating by industry.
<b>Application rate(s) and frequencies</b>	100 - 200 g/m <sup>2</sup> - 100 - Once.  100 - 200 g/m <sup>2</sup> - 100 - Once.
<b>Category(ies) of users</b>	Industrial  Trained professional  Professional
<b>Pack sizes and packaging material</b>	Can /Tin - Metal: - 5 - 25 L  Drum - Plastic: HDPE - 120 L

#### 4.1.1 Use-specific instructions for use

Authorisation is granted for use on windows, doors and conservatories only.  
The product can not be applied outside of dedicated treatment facilities.  
The product is for use on timbers not in ground contact, either continually exposed to the weather or protected from the weather but subject to frequent wetting.

#### 4.1.2 Use-specific risk mitigation measures

Treated timber must not be used in external situations where it is in contact with the ground and permanently exposed to wetting, or in permanent contact with fresh or salt water.  
Wear suitable protective clothing (coveralls, gloves, footwear) when applying the product and when handling freshly treated timber.  
Avoid excessive contamination of overalls.  
Wash hands and exposed skin before meals and after use.  
Unprotected persons and animals should be kept away from treated areas for 48 hours or until surface are dry.

#### 4.1.3 Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

Wood treated with this product may not be used over or near water bodies.  
Freshly treated timber must be stored after treatment under shelter or on an impermeable hard standing to prevent direct losses to water and that any losses (plus rainwater) must be collected for reuse or disposal.  
Do not contaminate ground, waterbodies or watercourses with chemicals or used container.

#### 4.1.4 Where specific to the use, the instructions for safe disposal of the product and its packaging

Dispose of surplus chemical, contaminated materials (including sawdust) and the empty container safely using a method approved by the waste disposal authority.  
Do not empty into drains.

#### 4.1.5 Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage

Keep in a safe place.

## **5. General directions for use**

### **5.1. Instructions for use**

As before.

### **5.2. Risk mitigation measures**

As before.

### **5.3. Particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment**

As before.

### **5.4. Instructions for safe disposal of the product and its packaging**

As before.

### **5.5. Conditions of storage and shelf-life of the product under normal conditions of storage**

As before.

## **6. Other information**