

Summary of product characteristics for a biocidal product family

Family name: HK-Lasur

Product type(s): PT08 - Wood preservatives (Preservatives)

Authorisation number: UK-2019-1208

R4BP 3 asset reference number: UK-0019792-0000

Table Of Contents

Part I.- First information level	1
1. Administrative information	1
1.1. Family name	1
1.2. Product type(s)	1
1.3. Authorisation holder	1
1.4. Manufacturer(s) of the biocidal products	1
1.5. Manufacturer(s) of the active substance(s)	2
2. Product family composition and formulation	2
2.1. Qualitative and quantitative information on the composition of the family	2
2.2. Type of formulation	2
Part II.- Second information level - meta SPC(s)	2
1. Meta SPC administrative information	2
1.1. Meta SPC identifier - META SPC1 - 1.5 % IPBC	2
1.2. Suffix to the authorisation number	2
1.3 Product type(s)	3
2. Meta SPC composition	3
2.1. Qualitative and quantitative information on the composition of the meta SPC	3
2.2. Type(s) of formulation of the meta SPC	3
3. Hazard and precautionary statements of the meta SPC	3
4. Authorised use(s) of the meta SPC	4
4.1.1 Use-specific instructions for use	5
4.1.2 Use-specific risk mitigation measures	5
4.1.3 Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment	5
4.1.4 Where specific to the use, the instructions for safe disposal of the product and its packaging	5
4.1.5 Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage	6
4.2.1 Use-specific instructions for use	7
4.2.2 Use-specific risk mitigation measures	7

4.2.3 Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment	7
4.2.4 Where specific to the use, the instructions for safe disposal of the product and its packaging	7
4.2.5 Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage	7
5. General directions for use of the meta SPC	8
5.1. Instructions for use	8
5.2. Risk mitigation measures	8
5.3. Particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment	8
5.4. Instructions for safe disposal of the product and its packaging	9
5.5. Conditions of storage and shelf-life of the product under normal conditions of storage	9
6. Other information	9
7. Third information level: individual products in the meta SPC	9
7.1 Trade name(s), authorisation number and specific composition of each individual product	9
7.1 Trade name(s), authorisation number and specific composition of each individual product	10
1.Meta SPC administrative information	12
1.1. Meta SPC identifier - META SPC 2 - 0,94 % IPBC	12
1.2. Suffix to the authorisation number	12
1.3 Product type(s)	12
2. Meta SPC composition	12
2.1.Qualitative and quantitative information on the composition of the meta SPC	12
2.2. Type(s) of formulation of the meta SPC	12
3. Hazard and precautionary statements of the meta SPC	12
4. Authorised use(s) of the meta SPC	13
4.1.1 Use-specific instructions for use	14
4.1.2 Use-specific risk mitigation measures	14
4.1.3 Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment	15
4.1.4 Where specific to the use, the instructions for safe disposal of the product and its packaging	15
4.1.5 Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage	15
4.2.1 Use-specific instructions for use	16
4.2.2 Use-specific risk mitigation measures	16

4.2.3 Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment	17
4.2.4 Where specific to the use, the instructions for safe disposal of the product and its packaging	17
4.2.5 Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage	17
5. General directions for use of the meta SPC	17
5.1. Instructions for use	17
5.2. Risk mitigation measures	17
5.3. Particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment	18
5.4. Instructions for safe disposal of the product and its packaging	18
5.5. Conditions of storage and shelf-life of the product under normal conditions of storage	19
6. Other information	19
7. Third information level: individual products in the meta SPC	19
7.1 Trade name(s), authorisation number and specific composition of each individual product	19

Part I.- First information level

1. Administrative information

1.1. Family name

HK-Lasur

1.2. Product type(s)

PT08 - Wood preservatives (Preservatives)

1.3. Authorisation holder

Name and address of the authorisation holder

Name	Remmers GmbH
Address	Bernhard-Remmers-Str. 13 D - 49624 Lönigen Germany

Authorisation number

UK-2019-1208

R4BP 3 asset reference number

UK-0019792-0000

Date of the authorisation

13/06/2019

Expiry date of the authorisation

30/06/2020

1.4. Manufacturer(s) of the biocidal products

Name of the manufacturer

Remmers GmbH

Address of the manufacturer

Bernhard-Remmers-Straße 13 49624 Lönigen Germany

Location of manufacturing sites

Bernhard-Remmers-Straße 13 49624 Lönigen Germany

1.5. Manufacturer(s) of the active substance(s)

Active substance	39 - 3-iodo-2-propynylbutylcarbamate (IPBC)
Name of the manufacturer	Troy Chemical Company BV
Address of the manufacturer	Uiverlaan 12E 3145 XN Maassluis Netherlands
Location of manufacturing sites	One Avenue L NJ, 07105 Newark United States

2. Product family composition and formulation

2.1. Qualitative and quantitative information on the composition of the family

Common name	IUPAC name	Function	CAS number	EC number	Content (%)
3-iodo-2-propynylbutylcarbamate (IPBC)		Active Substance	55406-53-6	259-627-5	0.94 - 1.5
White spirit	Naphtha (petroleum), hydrodesulfurized heavy		64742-82-1	265-185-4	28.9 - 38.85

2.2. Type(s) of formulation

AL - Any other liquid

Part II.- Second information level - meta SPC(s)

1. Meta SPC administrative information

1.1. Meta SPC identifier

META SPC1 - 1.5 % IPBC

1.2. Suffix to the authorisation number

1-1

1.3 Product type(s)

PT08 - Wood preservatives (Preservatives)

2. Meta SPC composition

2.1. Qualitative and quantitative information on the composition of the meta SPC

Common name	IUPAC name	Function	CAS number	EC number	Content (%)
3-iodo-2-propynylbutylcarbamate (IPBC)		Active Substance	55406-53-6	259-627-5	1.5 - 1.5
White spirit	Naphtha (petroleum), hydrodesulfurized heavy		64742-82-1	265-185-4	28.9 - 36.05

2.2. Type(s) of formulation of the meta SPC

Formulation(s)

AL - Any other liquid

3. Hazard and precautionary statements of the meta SPC

Hazard statements

May be fatal if swallowed and enters airways.
Causes skin irritation.
May cause an allergic skin reaction.
Harmful to aquatic life with long lasting effects.
Causes damage to organs central nervous system through prolonged or repeated exposure .
Repeated exposure may cause skin dryness or cracking.

Precautionary statements

If medical advice is needed, have product container or label at hand.
Keep out of reach of children.
Read carefully and follow all instructions.

Do not breathe vapours.

Wear protective clothing.

Avoid release to the environment.

IF SWALLOWED:Immediately call a POISON CENTER.

IF INHALED:Remove person to fresh air and keep comfortable for breathing.

If skin irritation or rash occurs:Get medical advice.

If eye irritation persists:Get medical attention.

Do NOT induce vomiting.

Dispose of contents to in accordance with local/regional/national/international regulations.

Wear protective gloves.

IF SWALLOWED:Immediately call a POISON CENTER.

If eye irritation persists:Get medical advice.

Dispose of contents to in accordance with local/regional/national/international regulations...

4. Authorised use(s) of the meta SPC

4.1 Use description

Use 1 - Preventive protection against wood-destroying and blue-staining fungi - professional use

Product type	PT08 - Wood preservatives (Preservatives)
Where relevant, an exact description of the authorised use	Preventive protection against wood destroying and blue stain fungi by spraying, and brushing in use class 2 and 3.
Target organism(s) (including development stage)	Aureobasidium pullulans spp.-Blue stain fungi-Hyphae Basidiomycetes:-Wood rotting basidiomycetes-Hyphae
Field(s) of use	Outdoor Target organism: preventive protection against wood-destroying and blue-staining fungi in UC 2 and 3 according to EN 335
Application method(s)	Open system: brush treatment - Target organisms: wood rotting fungi, blue stain fungi Field of use: Use Phase of treated Wood in Use Classes 2 and 3 acc. to EN 335, site of product application: outdoors, partly in situ

	Spraying - only in closed facilities Target organisms: wood rotting fungi, blue stain fungi Field of use: use Phase of treated wood in UC 2 and 3 according to EN 335, site of product application only at industrial indoor work places, no in situ application
Application rate(s) and frequencies	205-250 ml/m ² - 100 - Apply at least 2 subsequent coats. Drying-time brushing: Approximately 12 hours at 20°C/65% rel. humidity (increased drying time with lower temperature and higher 205-250 ml/m ² - 100 - Approximately 12 hours at 20°C/65% rel. humidity (increased drying time with lower temperature and higher humidity.)
Category(ies) of users	Trained professional Professional
Pack sizes and packaging material	Can /Tin, Metal: , 0.75 L, 2.5 L, 5 L, 10 L, 20 L Coated Tin Plate

4.1.1 Use-specific instructions for use

See section 5.1 below

4.1.2 Use-specific risk mitigation measures

Spraying application: Wear coated coveralls (protection of 90 %) and gloves.
 See section 5.2 below for further measures.

4.1.3 Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

See section 5.3 below

4.1.4 Where specific to the use, the instructions for safe disposal of the product and its packaging

See section 5.4 below

4.1.5 Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage

See section 5.5 below

4.2 Use description

Use 2 - Preventive protection against wood-destroying and blue stain fungi - industrial use

Product type	PT08 - Wood preservatives (Preservatives)
Where relevant, an exact description of the authorised use	Preventive protection against wood destroying and blue stain fungi by spraying, flow-coating and dipping in use class 2 and 3.
Target organism(s) (including development stage)	Aureobasidium pullulans spp.-Blue stain fungi-Hyphae Basidiomycetes:-Wood rotting basidiomycetes-Hyphae
Field(s) of use	Outdoor Target organism: preventive protection against wood-destroying and blue-staining fungi in UC 2 and 3 according to EN 335
Application method(s)	Open system: dip treatment - Target organisms: wood rotting fungi, blue stain fungi Field of use: use Phase of treated Wood in UC 2 and 3 according to EN 335, site of product application only at industrial indoor work places, no in situ application Open system: deluging - flow coating Target organisms: wood rotting fungi, blue stain fungi Field of use: use Phase of treated Wood in UC 2 and 3 according to EN 335, site of product application only at industrial indoor work places, no in situ application Spraying - only in closed facilities Target organisms: wood rotting fungi, blue stain fungi Field of use: use Phase of treated wood in UC 2 and 3 according to EN 335, site of product application only at industrial indoor work places, no in situ application
Application rate(s) and frequencies	205-250 ml/m ² - 100 - Drying time after application: Approximately 12 hours at 20°C/65% rel. humidity (increased drying time with lower temperature and higher humidity.) 205-250 ml/m ² - 100 - Approximately 12 hours at 20°C/65% rel. humidity (increased drying time with lower

	<p>temperature and higher humidity.)</p> <p>205-250 ml/m² - 100 - Approximately 12 hours at 20°C/65% rel. humidity (increased drying time with lower temperature and higher humidity.)</p>
Category(ies) of users	Industrial
Pack sizes and packaging material	<p>Can /Tin, Metal: , 0.75 L, 2.5 L, 5 L, 10 L, 20 L</p> <p>Coated Tin Plate</p>

4.2.1 Use-specific instructions for use

See section 5.1 below

4.2.2 Use-specific risk mitigation measures

Wear coated coveralls (protection of 90 %) and gloves.
Industrial application shall be conducted within a contained area on impermeable hard standing.
See section 5.2 below for further measures.

4.2.3 Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

See section 5.3 below

4.2.4 Where specific to the use, the instructions for safe disposal of the product and its packaging

See section 5.4 below

4.2.5 Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage

See section 5.5 below

5. General directions for use of the meta SPC

5.1. Instructions for use

Application rate 205-250 ml/m² (180-220 g/m²).
Drying-time brushing: Approximately 12 hours at 20°C/65% rel. humidity (increased drying time with lower temperature and higher humidity.)
Clean tool immediately after use with a thinner
Apply solvent-resistant skin protection cream to hands and arms before working to avoid skin cracking

5.2. Risk mitigation measures

Use only in well ventilated areas
Do not use indoor except for external windows frames and external doors.
Do not use on wood than comes in direct contact with food or feed.
Treated wood should not be intended for uses involving contact with food, feed or livestock.
Prevent any release to the environment during the product application phase as well as during the storage and the transport of treated timber.
Freshly treated timber shall be stored after treatment under shelter or on impermeable hard standing, or both, to prevent direct losses to soil, sewer or water, and any losses of the product shall be collected for reuse or disposal.

Any contaminated water/soil shall be collected, contained and treated as hazardous waste.
Open and handle with care
Do not eat, drink or smoke while working
Avoid contact with eyes and skin
Keep away from food, beverages and animal feed
Wash hands before pauses and after work
Do not inhale gases/vapours
Keep ignition sources away. – do not smoke
Protect against electrostatic charges
Fumes can combine with air to form an explosive mixture
In case of brief exposure or low pollution load, use respiratory protection equipment with filter. In case of intensive or longer exposure, use, self-contained respiratory protection equipment. Short term filter device: Filter A/P2
Eye protection: tightly sealed safety glasses.

5.3. Particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

HSL-30/mur
General information:
Immediately remove any clothing soiled by the product. In case of irregular breathing or respiratory arrest, provide artificial respiration. If symptoms occur or in case of doubt, seek medical attention. In case of unconsciousness, do not administer anything orally. Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
After inhalation:
Take affected persons into the open air and position comfortably. Seek medical treatment in case of complaints. In case of unconsciousness bring patient into stable side position for transport.
After skin contact:
Wash immediately with water and soap and rinse thoroughly. If skin irritation continues, consult a doctor.
After eye contact
Rinse opened eye for several minutes under running water. Then consult doctor.
After swallowing:
Do not induce vomiting. Do not give anything to drink. Call a doctor immediately! Keep the person affected quiet.
Information for doctor:
The following symptoms may occur:
In case of prolonged/repeated exposure or in high concentrations:
Headache
Dizziness
Dry skin
Irritating effect on skin and eyes.
Inhalation may have an irritating effect on mucous membranes.
Danger: Long-term or repeated exposure may cause inflammation of the skin (dermatitis).

Treatment: Symptomatic treatment
To avoid dermatitis (skin inflammation), use skin cream.

Measures for environmental protection:
Do not allow product to reach sewage system or water bodies. Do not allow to enter the ground/soil.
Prevent from spreading (e.g. by confining or oil barrier). This product may not be allowed to reach surface water because it is toxic to aquatic environments.

Measures for cleaning/collecting:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Send for recovery or disposal in suitable containers. Clean soiled surfaces with detergent. Treat washing liquid as special refuse. Place leaking containers in a marked drum or recovery drum. Ensure adequate ventilation.

5.4. Instructions for safe disposal of the product and its packaging

HSL-30/m
Disposal considerations
Product:
Recommendation:
Liquid material remains are to be disposed of at collection facilities for old varnishes. Do not dispose of together with household garbage. Do not allow product to reach sewage system. The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user's, other codes may apply under other conditions.
European waste catalogue:
03 02 02 organochlorinated wood preservatives
Uncleaned packaging:
Recommendation:
Only completely empty containers may be recycled. Disposal must be made according to official regulations.

5.5. Conditions of storage and shelf-life of the product under normal conditions of storage

HSL-30/m
Store in cool location.
Store away from food.
Store cool and dry in tightly closed containers.
Store container in a well-ventilated position.
Protect from frost.
Protect from heat and direct sunlight.
Smoking is prohibited in storage rooms.
Shelf life: 2 years

6. Other information

HSL-30/m - clear

7. Third information level: individual products in the meta SPC

7.1 Trade name(s), authorisation number and specific composition of each individual product

7.1 Trade name(s), authorisation number and specific composition of each individual product

Trade name(s)

HSL-30/m

Authorisation number

(R4BP 3 asset reference number - National Authorisation)

UK-0019792-0001 1-1

Common name	IUPAC name	Function	CAS number	EC number	Content (%)
3-iodo-2-propynylbutylcarbamate (IPBC)		Active Substance	55406-53-6	259-627-5	1.5
White spirit	Naphtha (petroleum), hydrodesulfurized heavy		64742-82-1	265-185-4	36.05

Trade name(s)

HSL-30/m - clear

Authorisation number

(R4BP 3 asset reference number - National Authorisation)

UK-0019792-0002 1-1

Common name	IUPAC name	Function	CAS number	EC number	Content (%)
3-iodo-2-propynylbutylcarbamate (IPBC)		Active Substance	55406-53-6	259-627-5	1.5
White spirit	Naphtha (petroleum), hydrodesulfurized heavy		64742-82-1	265-185-4	36.05

Trade name(s)

Only Dummy Product

Authorisation number

(R4BP 3 asset reference number - National Authorisation)

UK-0019792-0003 1-1

Common name	IUPAC name	Function	CAS number	EC number	Content (%)
3-iodo-2-propynylbutylcarbamate (IPBC)		Active Substance	55406-53-6	259-627-5	1.5
White spirit	Naphtha (petroleum), hydrodesulfurized heavy		64742-82-1	265-185-4	36.05

Trade name(s)

HK-Stain 1.5%

Authorisation number

(R4BP 3 asset reference number - National Authorisation)

UK-0019792-0007 1-1

Common name	IUPAC name	Function	CAS number	EC number	Content (%)
3-iodo-2-propynylbutylcarbamate (IPBC)		Active Substance	55406-53-6	259-627-5	1.5
White spirit	Naphtha (petroleum), hydrodesulfurized heavy		64742-82-1	265-185-4	36.05

1. Meta SPC administrative information

1.1. Meta SPC identifier

META SPC 2 - 0,94 % IPBC

1.2. Suffix to the authorisation number

1-2

1.3 Product type(s)

PT08 - Wood preservatives (Preservatives)

2. Meta SPC composition

2.1. Qualitative and quantitative information on the composition of the meta SPC

Common name	IUPAC name	Function	CAS number	EC number	Content (%)
3-iodo-2-propynylbutylcarbamate (IPBC)		Active Substance	55406-53-6	259-627-5	0.94 - 0.94
White spirit	Naphtha (petroleum), hydrodesulfurized heavy		64742-82-1	265-185-4	31.7 - 38.85

2.2. Type(s) of formulation of the meta SPC

Formulation(s)

AL - Any other liquid

3. Hazard and precautionary statements of the meta SPC

Hazard statements

May be fatal if swallowed and enters airways.
Causes skin irritation.
Harmful to aquatic life with long lasting effects.
Causes damage to organs central nervous system through prolonged or repeated exposure .

Precautionary statements

Repeated exposure may cause skin dryness or cracking. Causes serious eye irritation. Contains IPBC. May produce an allergic reaction.
If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read carefully and follow all instructions. Do not breathe vapours. Wear protective clothing. Avoid release to the environment. IF SWALLOWED:Immediately call a POISON CENTER. IF INHALED:Remove person to fresh air and keep comfortable for breathing. If skin irritation or rash occurs:Get medical advice. If eye irritation persists:Get medical attention. Do NOT induce vomiting. Dispose of contents to in accordance with local/regional/national/international regulations. Wear protective gloves. IF SWALLOWED:Immediately call a POISON CENTER. If eye irritation persists:Get medical advice. Dispose of contents to in accordance with local/regional/national/international regulations...

4. Authorised use(s) of the meta SPC

4.1 Use description

Use 1 - Preventive protection against blue stain fungi - professional use

Product type

PT08 - Wood preservatives (Preservatives)

Where relevant, an exact description of the authorised use

Preventive protection against blue stain fungi by spraying and brushing in use class 2 and 3.

Target organism(s) (including development stage)

Aureobasidium pullulans spp.-Blue stain fungi-Hyphae
--

Field(s) of use	Outdoor Target organism: preventive protection against blue-staining fungi in UC 2 and 3 according to EN 335
Application method(s)	Open system: brush treatment - Target organisms: blue stain fungi Field of use: Use Phase of treated Wood in Use Classes 2 and 3 acc. to EN 335, site of product application: outdoors, partly in situ Spraying - only in closed facilities Target organisms: blue stain fungi Field of use: use Phase of treated wood in UC 2 and 3 according to EN 335, site of product application only at industrial indoor work places, no in situ application
Application rate(s) and frequencies	205-250 ml/m ² - 100 - Apply at least 2 subsequent coats. Drying-time brushing: Approximately 12 hours at 20°C/65% rel. humidity (increased drying time with lower temperature and higher 205-250 ml/m ² - 100 - Drying time: Approximately 12 hours at 20°C/65% rel. humidity (increased drying time with lower temperature and higher humidity.)
Category(ies) of users	Trained professional Professional
Pack sizes and packaging material	Can /Tin, coated tin plate , 0.75 L, 2.5 L, 5L coated tin plate Maximum package size for consumer use: 10 L

4.1.1 Use-specific instructions for use

See section 5.1 below

4.1.2 Use-specific risk mitigation measures

Spraying application: Wear coated coveralls (protection of 90 %) and gloves.
See section 5.2 below for further measures.

4.1.3 Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

See section 5.3 below

4.1.4 Where specific to the use, the instructions for safe disposal of the product and its packaging

See section 5.4 below

4.1.5 Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage

See section 5.1 below

4.2 Use description

Use 2 - Preventive protection against blue stain fungi - industrial use

Product type	PT08 - Wood preservatives (Preservatives)
Where relevant, an exact description of the authorised use	Preventive protection against blue stain fungi by spraying, flow-coating and dipping in use class 2 and 3.
Target organism(s) (including development stage)	Aureobasidium pullulans spp.-Blue stain fungi-Hyphae
Field(s) of use	Outdoor Target organism: preventive protection against blue-staining fungi in UC 2 and 3 according to EN 335
Application method(s)	Open system: dip treatment - Target organisms: blue stain fungi Field of use: use Phase of treated Wood in UC 2 and 3 according to EN 335, site of product application only at industrial indoor work places, no in situ application

	<p>Open system: deluging - flow coating Target organisms: blue stain fungi Field of use: use Phase of treated Wood in UC 2 and 3 according to EN 335, site of product application only at industrial indoor work places, no in situ application</p> <p>Spraying - only in closed facilities Target organisms: blue stain fungi Field of use: use Phase of treated wood in UC 2 and 3 according to EN 335, site of product application only at industrial indoor work places, no in situ application</p>
<p>Application rate(s) and frequencies</p>	<p>205-250 ml/m² - 100 - Drying time after application: Approximately 12 hours at 20°C/65% rel. humidity (increased drying time with lower temperature and higher humidity.)</p> <p>205-250 ml/m² - 100 - Drying time: Approximately 12 hours at 20°C/65% rel. humidity (increased drying time with lower temperature and higher humidity.)</p> <p>205-250 ml/m² - 100 - Drying time: Approximately 12 hours at 20°C/65% rel. humidity (increased drying time with lower temperature and higher humidity.)</p>
<p>Category(ies) of users</p>	<p>Industrial</p>
<p>Pack sizes and packaging material</p>	<p>Can /Tin, coated tin plate , 0.75 L, 2.5 L, 5L</p> <p>coated tin plate</p> <p>Maximum package size for consumer use: 10 L</p>

4.2.1 Use-specific instructions for use

See section 5.1 below

4.2.2 Use-specific risk mitigation measures

Wear coated coveralls (protection of 90 %) and gloves.
Industrial application shall be conducted within a contained area on impermeable hard standing.
See section 5.2 below for further measures.

4.2.3 Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

See section 5.3 below

4.2.4 Where specific to the use, the instructions for safe disposal of the product and its packaging

See section 5.4 below

4.2.5 Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage

See section 5.5 below

5. General directions for use of the meta SPC

5.1. Instructions for use

Application rate 205-250 ml/m² (180-220 g/m²).
Drying-time brushing: Approximately 12 hours at 20°C/65% rel. humidity (increased drying time with lower temperature and higher humidity.)
Clean tool immediately after use with a thinner
Apply solvent-resistant skin protection cream to hands and arms before working to avoid skin cracking

5.2. Risk mitigation measures

Use only in well ventilated areas
Do not use indoor except for external windows frames and external doors.
Do not use on wood than comes in direct contact with food or feed.
Treated wood should not be intended for uses involving contact with food, feed or livestock.

Prevent any release to the environment during the product application phase as well as during the storage and the transport of treated timber.
Industrial application shall be conducted within a contained area on impermeable hard standing.
Freshly treated timber shall be stored after treatment under shelter or on impermeable hard standing, or both, to prevent direct losses to soil, sewer or water, and any losses of the product shall be collected for reuse or disposal.
Any contaminated water/soil shall be collected, contained and treated as hazardous waste.
Open and handle with care
Do not eat, drink or smoke while working
Avoid contact with eyes and skin
Keep away from food, beverages and animal feed
Wash hands before pauses and after work
Do not inhale gases/vapours
Keep ignition sources away. – do not smoke
Protect against electrostatic charges
Fumes can combine with air to form an explosive mixture

5.3. Particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

HK-Lasur
General information:
Immediately remove any clothing soiled by the product. In case of irregular breathing or respiratory arrest, provide artificial respiration. If symptoms occur or in case of doubt, seek medical attention. In case of unconsciousness, do not administer anything orally. Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
After inhalation:
Take affected persons into the open air and position comfortably. Seek medical treatment in case of complaints. In case of unconsciousness bring patient into stable side position for transport.
After skin contact:
Wash immediately with water and soap and rinse thoroughly. If skin irritation continues, consult a doctor.
After eye contact
Rinse opened eye for several minutes under running water. Then consult doctor.
After swallowing:
Do not induce vomiting. Do not give anything to drink. Call a doctor immediately! Keep the person affected quiet.
Information for doctor:
The following symptoms may occur:
In case of prolonged/repeated exposure or in high concentrations:
Headache
Dizziness
Dry skin
Irritating effect on skin and eyes.
Inhalation may have an irritating effect on mucous membranes.
Danger: Long-term or repeated exposure may cause inflammation of the skin (dermatitis).
Treatment: Symptomatic treatment
To avoid dermatitis (skin inflammation), use skin cream.

Measures for environmental protection:
Do not allow product to reach sewage system or water bodies. Do not allow to enter the ground/soil. Prevent from spreading (e.g. by confining or oil barrier). This product may not be allowed to reach surface water because it is toxic to aquatic environments.
Measures for cleaning/collecting:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Send for recovery or disposal in suitable containers. Clean soiled surfaces with detergent. Treat washing liquid as special refuse. Place leaking containers in a marked drum or recovery drum. Ensure adequate ventilation.

5.4. Instructions for safe disposal of the product and its packaging

HK-Lasur
Disposal considerations
Product:
Recommendation:
Liquid material remains are to be disposed of at collection facilities for old varnishes. Do not dispose of together with household garbage. Do not allow product to reach sewage system. The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user's, other codes may apply under other conditions.

European waste catalogue:
03 02 02 organochlorinated wood preservatives
Uncleaned packaging:
Recommendation:
Only completely empty containers may be recycled. Disposal must be made according to official regulations.

5.5. Conditions of storage and shelf-life of the product under normal conditions of storage

HK-Lasur
Store in cool location.
Store away from food.
Store cool and dry in tightly closed containers.
Store container in a well-ventilated position.
Protect from frost.
Protect from heat and direct sunlight.
Smoking is prohibited in storage rooms.
Shelf life: 2 years

6. Other information

7. Third information level: individual products in the meta SPC

7.1 Trade name(s), authorisation number and specific composition of each individual product

Trade name(s)	HK-Lasur
Authorisation number <small>(R4BP 3 asset reference number - National Authorisation)</small>	UK-0019792-0004 1-2

Common name	IUPAC name	Function	CAS number	EC number	Content (%)
3-iodo-2-propynylbutylcarbamate (IPBC)		Active Substance	55406-53-6	259-627-5	0.94

White spirit	Naphtha (petroleum), hydrodesulfurized heavy	64742-82-1	265-185-4	38.85
--------------	---	------------	-----------	-------

Trade name(s)

HK-Lasur - clear

Authorisation number

UK-0019792-0005 1-2

(R4BP 3 asset reference number - National
Authorisation)

Common name	IUPAC name	Function	CAS number	EC number	Content (%)
3-iodo-2-propynylbutylcarbamate (IPBC)		Active Substance	55406-53-6	259-627-5	0.94
White spirit	Naphtha (petroleum), hydrodesulfurized heavy		64742-82-1	265-185-4	36.05

Trade name(s)

Only DUMMY product

Authorisation number

UK-0019792-0006 1-2

(R4BP 3 asset reference number - National
Authorisation)

Common name	IUPAC name	Function	CAS number	EC number	Content (%)
3-iodo-2-propynylbutylcarbamate (IPBC)		Active Substance	55406-53-6	259-627-5	0.94
White spirit	Naphtha (petroleum), hydrodesulfurized heavy		64742-82-1	265-185-4	34.85

Trade name(s)

HK-Stain

Authorisation number

UK-0019792-0008 1-2

(R4BP 3 asset reference number - National
Authorisation)

Common name	IUPAC name	Function	CAS number	EC number	Content (%)
3-iodo-2-propynylbutylcarbamate (IPBC)		Active Substance	55406-53-6	259-627-5	0.94
White spirit	Naphtha (petroleum), hydrodesulfurized heavy		64742-82-1	265-185-4	34.85
