Summary of product characteristics for a biocidal product

Product name: Sikkens Cetol HLS plus (BP) (Oregon)

Product type(s): PT08 - Wood preservatives (Preservatives)

Authorisation number: 2248-2

R4BP 3 asset reference number: BG-0014791-0009

Table Of Contents

Administrative information	1
1.1. Trade names of the product	1
1.2. Authorisation holder	1
1.3. Manufacturer(s) of the biocidal products	1
1.4. Manufacturer(s) of the active substance(s)	1
2. Product composition and formulation	2
2.1. Qualitative and quantitative information on the composition of the biocidal product	2
2.2. Type of formulation	3
3. Hazard and precautionary statements	3
4. Authorised use(s)	4
5. General directions for use	34
5.1. Instructions for use	
	34
5.2. Risk mitigation measures	35
5.3. Particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment	36
5.4. Instructions for safe disposal of the product and its packaging	39
5.5. Conditions of storage and shelf-life of the product under normal conditions of storage	41
6. Other information	43

Administrative information

1.1. Trade names of the product

Sikkens Cetol HLS plus(BP) Oregon

Xyladecor Holzschutzlasur BPR Oregon

1.2. Authorisation holder

Name and address of the authorisation holder

Address Christian Neefestraat 2 - Attn. Director PSRA Amsterdam Netherlands	RAQ 1077 WW

Authorisation number

R4BP 3 asset reference number

Date of the authorisation

Expiry date of the authorisation

BG-0014791-0009	
22/06/2015	
31/07/2025	I

1.3. Manufacturer(s) of the biocidal products

Name of the manufacturer Akzo

Akzo Nobel Decorative Paints

2248-2 1-1

Address of the manufacturer

Z.I. "Les Bas Prés", C.S. 70113 60160 Montataire France

Location of manufacturing sites

Z.I. "Les Bas Prés", C.S. 70113 60160 Montataire France

1.4. Manufacturer(s) of the active substance(s)

Active substance	39 - 3-iodo-2-propynylbutylcarbamate (IPBC)
Name of the manufacturer	TROY Corporation
Address of the manufacturer	8 Vreeland Road, Florham Park 07932 New Jersey United States
Location of manufacturing sites	One Avenue L NJ 07105 Newark United States
Active substance	39 - 3-iodo-2-propynylbutylcarbamate (IPBC)
Name of the manufacturer	TROY Chemical Corporation
Address of the manufacturer	One Avenue L NJ 07105 Newark United States
Location of manufacturing sites	12e Uiverlaan 3145 Maassluis Netherlands

2. Product composition and formulation

2.1. Qualitative and quantitative information on the composition of the biocidal product

IUPAC name	Function	CAS number	EC number	Content (%)
	Active Substance	55406-53-6	259-627-5	0,7
	Non-active substance	64742-47-8		22,199
	Non-active substance	96-29-7		0,388
Alkyd solution	Non-active substance			35,86
	Non-active substance	8001-26-1		2,5
	Non-active substance	68953-58-2		0,571
	Non-active substance	8002-43-5		0,057
	Non-active substance	68551-41-7		1,99
		Active Substance Non-active substance	Active Substance 55406-53-6 Non-active substance 64742-47-8 Non-active substance 96-29-7 Alkyd solution Non-active substance 8001-26-1 Non-active substance 68953-58-2 Non-active substance 8002-43-5 Non-active substance 68551-41-7	Active Substance 55406-53-6 259-627-5 Non-active substance 64742-47-8

Non-active substance	22464-99-9	1,994
Non-active substance	15956-58-8	0,1
Non-active substance	64741-65-7	0,2
Non-active substance	9011-05-6	1,5
Non-active substance	10034-99-8	0,14
Non-active substance		1,633
Non-active substance	7732-18-5	28,02
Non-active substance	127519-17-9	0,2
Non-active substance	129757-67-1	0,1
Non-active substance	96556-05-7	0,67
Non-active substance	1333-86-4	0,007
Non-active substance	1309-37-1	0,13
Non-active substance	20344-49-4	1,037
Non-active substance	13463-67-7	0
Non-active substance	147-14-8	0
Non-active substance	980-26-7	0
Non-active substance	1328-53-6	0
Non-active substance	6358-30-1	0
	substance Non-active substance	substance 22464-99-9 Non-active substance 15956-58-8 Non-active substance 64741-65-7 Non-active substance 10034-99-8 Non-active substance 10034-99-8 Non-active substance 7732-18-5 Non-active substance 127519-17-9 Non-active substance 129757-67-1 Non-active substance 96556-05-7 Non-active substance 1309-37-1 Non-active substance 20344-49-4 Non-active substance 13463-67-7 Non-active substance 147-14-8 Non-active substance 980-26-7 Non-active substance 1328-53-6 Non-active substance 1328-53-6

2.2. Type of formulation

AL - Any other liquid

3. Hazard and precautionary statements

Hazard statements

Harmful to aquatic life with long lasting effects.

Repeated exposure may cause skin dryness or cracking.

Contains 3-iodo-2-propynyl butylcarbamate and 2-butanone oxime. May produce an allergic reaction.

Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Do not get in eyes, on skin, or on clothing.

Avoid release to the environment.

Call a POISON CENTER if you feel unwell.

Dispose of contents to local rules.

Call a POISON CENTER if you feel unwell.

Dispose of container to local rules.

4. Authorised use(s)

4.1 Use description

Use 1 - Against wood discolouring fungi

Product type	PT08 - Wood preservatives (Preservatives)
Where relevant, an exact description of the authorised use	For all outside wood, which is not I direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and outer parts), carports, shutters and balcony railings. Not for indoor use.
Target organism(s) (including development stage)	Scientific name: Aureobasidium pullulans spp. Common name: Sapstain fungi Development stage:
Field(s) of use	Indoor Outdoor
Application method(s)	Method: Open system: brush treatment Detailed description: Not available
Application rate(s) and frequencies	Application Rate: 200-250 ml/m² Dilution (%): No dilution Number and timing of application:

	200-250 g/m²
Category(ies) of users	Professional General public (non-professional)
Pack sizes and packaging	Can /Tin, Metal: , 0.75L - 20L (0.75L; 1L; 2.5L; 3L; 5L; 5.5L; 6L; 9L; 9.5L; 10L; 11L; 11.5L; 12L; 20L)

Pack sizes and pag material

4.1.1 Use-specific instructions for use

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and outer parts), carports, shutters and balcony railings. Not for indoor use.

4.1.2 Use-specific risk mitigation measures

Keep out of reach of children. Wear suitable protective clothing and gloves

4.1.3 Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur.

If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs.

After inhalation: Move affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

4.1.4 Where specific to the use, the instructions for safe disposal of the product and its packaging

European waste code (EWC): 03 02 05: other wood preservatives containing dangerous substances / 20 01 27: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

4.1.5 Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage

Store product in tightly closed original containers at temperatures about 5 - 30° C. The product is stable for 3 years at room temperature.

4.2 Use description

Use 2 - Against wood discolouring fungi

Product type	PT08 - Wood preservatives (Preservatives)
Where relevant, an exact description of the authorised use	Not available
Target organism(s) (including development stage)	Scientific name: Common name: wood discolouring fungi Development stage: Not available
Field(s) of use	Indoor Outdoor
Application method(s)	Method: Open system: brush treatment Detailed description: Not available
Application rate(s) and frequencies	Application Rate: 200-250 ml/m2 Dilution (%): 0 Number and timing of application: 200-250 g/m2
Category(ies) of users	Professional General public (non-professional)
Pack sizes and packaging material	can, not available , 1 1-20L

4.2.1 Use-specific instructions for use

see other section			
4.2.2 Use-specific risk mitiga	ation measures		
see other section			
<u>-</u>	4.2.3 Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment		
see other section			
4.2.4 Where specific to the uspeckaging	se, the instructions for safe disposal of the product and its		
see other section			
I.2.5 Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage			
see other section			
4.3 Use description			
Use 3 - Against wood discolour	ing fungi		
Product type	PT08 - Wood preservatives (Preservatives)		
Where relevant, an exact description of the authorised use	Not available		
Target organism(s) (including development stage)	Scientific name: Common name: wood discolouring fungi Development stage: Not available		
Field(s) of use	Indoor Outdoor		
Application method(s)	Method: Open system: brush treatment Detailed description: Not available		

Application rate(s) and frequencies	Application Rate: 200-250 ml/m2 Dilution (%): 0 Number and timing of application: 200-250 g/m2	
Category(ies) of users	Professional	
5	General public (non-professional)	
Pack sizes and packaging material	can, not available , 1	
	1-20L	
4.3.1 Use-specific instructio	ons for use	
see other section		
4.3.2 Use-specific risk mitig	ation measures	
see other section		
	use, the particulars of likely direct or indirect effects, first aid measures to protect the environment	
see other section		
4.3.4 Where specific to the upackaging	use, the instructions for safe disposal of the product and its	
see other section		
4.3.5 Where specific to the under normal conditions of	ise, the conditions of storage and shelf-life of the product storage	
see other section		

4.4 Use description

Use 4 - Against wood discolouring fungi

Product type	PT08 - Wood preservatives (Preservatives)
Where relevant, an exact description of the authorised use	Not available
Target organism(s) (including development stage)	Scientific name: Common name: wood discolouring fungi Development stage: Not available
Field(s) of use	Indoor Outdoor
Application method(s)	Method: Open system: brush treatment Detailed description: Not available
Application rate(s) and frequencies	Application Rate: 200-250 ml/m2 Dilution (%): 0 Number and timing of application: 200-250 g/m2
Category(ies) of users	Professional General public (non-professional)
Pack sizes and packaging material	can, not available , 1 1-20L

4.4.1 Use-specific instructions for use

see other section

4.4.2 Use-specific risk mitigation measures

see other section		
4.4.3 Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment		
see other section		
4.4.4 Where specific to the uspackaging	se, the instructions for safe disposal of the product and its	
see other section		
4.4.5 Where specific to the us under normal conditions of s	se, the conditions of storage and shelf-life of the product torage	
see other section		
4.5 Use description Use 5 - Against wood discolour	ing fungi	
Product type	PT08 - Wood preservatives (Preservatives)	
Where relevant, an exact description of the authorised use	Not available	
Target organism(s) (including development stage)	Scientific name: Common name: wood discolouring fungi Development stage: Not available	
Field(s) of use	Indoor Outdoor	
Application method(s)	Method: Open system: brush treatment Detailed description: Not available	
Application rate(s) and frequencies	Application Rate: 200-250 ml/m2 Dilution (%): 0 Number and timing of application: 200-250 g/m2	

Category(ies) of users	Professional		
	General public (non-professional)		
Pack sizes and packaging material	can, not available , 1		
materiai	1-20L		
4.5.1 Use-specific instruction	ons for use		
see other section			
4.5.2 Use-specific risk mitiç	gation measures		
see other section	see other section		
	use, the particulars of likely direct or indirect effects, first aid y measures to protect the environment		
see other section			
4.5.4 Where specific to the packaging	use, the instructions for safe disposal of the product and its		
see other section			
4.5.5 Where specific to the under normal conditions of	use, the conditions of storage and shelf-life of the product storage		
see other section			
4.6 Use description			
Use 6 - Against wood discolo	uring fungi		
Product type	PT08 - Wood preservatives (Preservatives)		

Where relevant, an exact description of the authorised use	Not available	
Target organism(s) (including development stage)	Scientific name: Common name: wood discolouring fungi Development stage: Not available	
Field(s) of use	Indoor Outdoor	
Application method(s)	Method: Open system: brush treatment Detailed description: Not available	
Application rate(s) and frequencies	Application Rate: 200-250 ml/m2 Dilution (%): 0 Number and timing of application: 200-250 g/m2	
Category(ies) of users	Professional General public (non-professional)	
Pack sizes and packaging material	can, not available , 1 1-20L	
4.6.1 Use-specific instructions for use		
see other section		
4.6.2 Use-specific risk mitigation measures		
see other section		

4.6.3 Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

see other section		
4.6.4 Where specific to the u packaging	se, the instructions for safe disposal of the product and its	
see other section		
4.6.5 Where specific to the us under normal conditions of s	se, the conditions of storage and shelf-life of the product storage	
see other section		
4.7 Use description		
Use 7 - Against wood discolour	ing fungi	
Product type	PT08 - Wood preservatives (Preservatives)	
Where relevant, an exact description of the authorised use	Not available	
Target organism(s) (including development stage)	Scientific name: Common name: wood discolouring fungi Development stage: Not available	
Field(s) of use	Indoor Outdoor	
Application method(s)	Method: Open system: brush treatment Detailed description: Not available	
Application rate(s) and frequencies	Application Rate: 200-250 ml/m2 Dilution (%): 0 Number and timing of application: 200-250 g/m2	
Category(ies) of users	Professional General public (non-professional)	

can, not available , 1

Pack sizes and packaging material

4.7.1 Use-specific instructions for use		
see other section		
4.7.2 Use-specific risk mitiga	ation measures	
see other section		
•	se, the particulars of likely direct or indirect effects, first aid measures to protect the environment	
see other section		
4.7.4 Where specific to the u packaging	se, the instructions for safe disposal of the product and its	
see other section		
4.7.5 Where specific to the us under normal conditions of s	se, the conditions of storage and shelf-life of the product storage	
see other section		
4.8 Use description Use 8 - Against wood discolour	ring fungi	
Product type	PT08 - Wood preservatives (Preservatives)	
Where relevant, an exact description of the authorised use	Not available	
Target organism(s) (including development stage)	Scientific name: Common name: wood discolouring fungi Development stage: Not available	

1-20L

Field(s) of use	Indoor Outdoor	
Application method(s)	Method: Open system: brush treatment Detailed description: Not available	
Application rate(s) and frequencies	Application Rate: 200-250 ml/m2 Dilution (%): 0 Number and timing of application: 200-250 g/m2	
Category(ies) of users	Professional	
	General public (non-professional)	
Pack sizes and packaging material	can, not available , 1	
materiai	1-20L	
4.8.1 Use-specific instructions for use		
see other section		
4.8.2 Use-specific risk mitigation measures		
see other section		
4.8.3 Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment		
see other section		
4.8.4 Where specific to the use, the instructions for safe disposal of the product and its packaging		
see other section		

4.8.5 Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage

see other section		

4.9 Use description			
Use 9 - Against wood discolour	Use 9 - Against wood discolouring fungi		
Product type	PT08 - Wood preservatives (Preservatives)		
Where relevant, an exact description of the authorised use	Not available		
Target organism(s) (including development stage)	Scientific name: Common name: wood discolouring fungi Development stage: Not available		
Field(s) of use	Indoor Outdoor		
Application method(s)	Method: Open system: brush treatment Detailed description: Not available		
Application rate(s) and frequencies	Application Rate: 200-250 ml/m2 Dilution (%): 0 Number and timing of application: 200-250 g/m2		
Category(ies) of users	Professional General public (non-professional)		
Pack sizes and packaging material	can, not available , 1 1-20L		

4.9.1 Use-specific instructions for use			
see other section			
4.9.2 Use-specific risk mitigation measures			
see other section			
-	ise, the particulars of likely direct or indirect effects, first aid measures to protect the environment		
see other section			
4.9.4 Where specific to the upackaging	ise, the instructions for safe disposal of the product and its		
see other section			
	4.9.5 Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage		
see other section			
4.10 Use description			
Use 10 - Against wood discolor	uring fungi		
Product type	PT08 - Wood preservatives (Preservatives)		
Where relevant, an exact description of the authorised use	Not available		
Target organism(s) (including development stage)	Scientific name: Common name: wood discolouring fungi Development stage: Not available		
Field(s) of use	Indoor Outdoor		
Application method(s)	Method: Open system: brush treatment Detailed description:		

	Not available		
Application rate(s) and frequencies	Application Rate: 200-250 ml/m2 Dilution (%): 0 Number and timing of application: 200-250 g/m2		
Category(ies) of users	Professional General public (non-professional)		
Pack sizes and packaging material	can, not available , 1		
4.10.1 Use-specific instruction	ons for use		
see other section			
4.10.2 Use-specific risk mitigation measures			
see other section			
4.10.3 Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment			
see other section	see other section		
4.10.4 Where specific to the use, the instructions for safe disposal of the product and its packaging			
see other section			
4.10.5 Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage			
see other section			

4.11 Use description

Use 11 - Against wood discolouring fungi

Product type	PT08 - Wood preservatives (Preservatives)
Where relevant, an exact description of the authorised use	Not available
Target organism(s) (including development stage)	Scientific name: Common name: wood discolouring fungi Development stage: Not available
Field(s) of use	Indoor Outdoor
Application method(s)	Method: Open system: brush treatment Detailed description: Not available
Application rate(s) and frequencies	Application Rate: 200-250 ml/m2 Dilution (%): 0 Number and timing of application: 200-250 g/m2
Category(ies) of users	Professional General public (non-professional)
Pack sizes and packaging material	can, not available , 1 1-20L

4.11.1 Use-specific instructions for use

see other section

4.11.2 Use-specific risk mitigation measures

see other section		
4.11.3 Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment		
see other section		
4.11.4 Where specific to the packaging	use, the instructions for safe disposal of the product and its	
see other section		
4.11.5 Where specific to the ເ under normal conditions of s	use, the conditions of storage and shelf-life of the product torage	
see other section		
4.12 Use description Use 12 - Against wood discolou	PT08 - Wood preservatives (Preservatives)	
Product type Where relevant, an exact description of the authorised use	Not available	
Target organism(s) (including development stage)	Scientific name: Common name: wood discolouring fungi Development stage: Not available	
Field(s) of use	Indoor Outdoor	
Application method(s)	Method: Open system: brush treatment Detailed description: Not available	
Application rate(s) and frequencies	Application Rate: 200-250 ml/m2 Dilution (%): 0 Number and timing of application: 200-250 g/m2	

Category(ies) of users	Professional
	General public (non-professional)
Pack sizes and packaging material	can, not available , 1
	1-20L
4.12.1 Use-specific instruction	ons for use
see other section	
4.12.2 Use-specific risk mitiç	gation measures
see other section	
-	use, the particulars of likely direct or indirect effects, first aid measures to protect the environment
see other section	
4.12.4 Where specific to the packaging	use, the instructions for safe disposal of the product and its
see other section	
I.12.5 Where specific to the under normal conditions of s	use, the conditions of storage and shelf-life of the product storage
see other section	
4.13 Use description	
Use 13 - Against wood discolo	uring fungi
Product type	PT08 - Wood preservatives (Preservatives)

Where relevant, an exact description of the authorised use	Not available
Target organism(s) (including development stage)	Scientific name: Common name: wood discolouring fungi Development stage: Not available
Field(s) of use	Indoor Outdoor
Application method(s)	Method: Open system: brush treatment Detailed description: Not available
Application rate(s) and frequencies	Application Rate: 200-250 ml/m2 Dilution (%): 0 Number and timing of application: 200-250 g/m2
Category(ies) of users	Professional General public (non-professional)
Pack sizes and packaging material	can, not available , 1 1-20L
4.13.1 Use-specific instructions for use	
see other section	
4.13.2 Use-specific risk mitigation measures	
see other section	

4.13.3 Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

see other section	
4.13.4 Where specific to the packaging	use, the instructions for safe disposal of the product and its
see other section	
4.13.5 Where specific to the ເ under normal conditions of s	use, the conditions of storage and shelf-life of the product storage
see other section	
4.14 Use description	
Use 14 - Against wood discolou	ıring fungi
Product type	PT08 - Wood preservatives (Preservatives)
Where relevant, an exact description of the authorised use	Not available
Target organism(s) (including development stage)	Scientific name: Common name: wood discolouring fungi Development stage: Not available
Field(s) of use	Indoor Outdoor
Application method(s)	Method: Open system: brush treatment Detailed description: Not available
Application rate(s) and frequencies	Application Rate: 200-250 ml/m2 Dilution (%): 0 Number and timing of application: 200-250 g/m2
Category(ies) of users	Professional General public (non-professional)

can, not available , 1

Pack sizes and packaging material

4.14.1 Use-specific instruction	ons for use
see other section	
4.14.2 Use-specific risk mitig	ation measures
see other section	
-	use, the particulars of likely direct or indirect effects, first aid measures to protect the environment
see other section	
4.14.4 Where specific to the packaging	use, the instructions for safe disposal of the product and its
see other section	
4.14.5 Where specific to the u under normal conditions of s	use, the conditions of storage and shelf-life of the product storage
see other section	
4.15 Use description Use 15 - Against wood discolou	uring fungi
OSC 13 - Agamst Wood discolor	PT08 - Wood preservatives (Preservatives)
Product type	1 100 WOOD preservatives (1 reservatives)
Where relevant, an exact description of the authorised use	Not available
Target organism(s) (including development stage)	Scientific name: Common name: wood discolouring fungi Development stage: Not available

1-20L

Field(s) of use	Indoor	
	Outdoor	
Application method(s)	Method: Open system: brush treatment Detailed description:	
	Not available	
Application rate(s) and frequencies	Application Rate: 200-250 ml/m2 Dilution (%): 0	
пециспојез	Number and timing of application: 200-250 g/m2	
	Professional	
Category(ies) of users	General public (non-professional)	
	General public (non-professional)	
Pack sizes and packaging	can, not available , 1	
material		
	1-20L	
4.15.1 Use-specific instruction	one for use	
4.13.1 030-3pccmc mandend	ons for use	
see other section		
4.15.2 Use-specific risk mitig	jation measures	
see other section		
See onici Section		
4.15.3 Where specific to the	use, the particulars of likely direct or indirect effects, first aid	
instructions and emergency	measures to protect the environment	
see other section		
4.15.4 Where specific to the use, the instructions for safe disposal of the product and its		
packaging		
see other section		

4.15.5 Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage

see other section		

ouring fungi
PT08 - Wood preservatives (Preservatives)
Not available
Scientific name: Common name: wood discolouring fungi Development stage: Not available
Indoor Outdoor
Method: Open system: brush treatment Detailed description: Not available
Application Rate: 200-250 ml/m2 Dilution (%): 0 Number and timing of application: 200-250 g/m2
Professional General public (non-professional)
can, not available , 1 1-20L

4.16.1 Use-specific instructions for use		
see other section		
4.16.2 Use-specific risk mitig	gation measures	
see other section		
-	use, the particulars of likely direct or indirect effects, first aid measures to protect the environment	
see other section		
4.16.4 Where specific to the packaging	use, the instructions for safe disposal of the product and its	
see other section		
4.16.5 Where specific to the under normal conditions of s	use, the conditions of storage and shelf-life of the product storage	
see other section		
4.17 Use description		
Use 17 - Against wood discolo	uring fungi	
Product type	PT08 - Wood preservatives (Preservatives)	
Where relevant, an exact description of the authorised use	Not available	
Target organism(s) (including development stage)	Scientific name: Common name: wood discolouring fungi Development stage: Not available	
Field(s) of use	Indoor Outdoor	
Application method(s)	Method: Open system: brush treatment Detailed description:	

	Not available	
Application rate(s) and frequencies	Application Rate: 200-250 ml/m2 Dilution (%): 0 Number and timing of application: 200-250 g/m2	
Category(ies) of users	Professional General public (non-professional)	
Pack sizes and packaging material	can, not available , 1	
4.17.1 Use-specific instructions for use		
see other section		
4.17.2 Use-specific risk mitig	ation measures	
see other section		
	use, the particulars of likely direct or indirect effects, first aid measures to protect the environment	
see other section		
4.17.4 Where specific to the packaging	use, the instructions for safe disposal of the product and its	
see other section		
4.17.5 Where specific to the u under normal conditions of s	use, the conditions of storage and shelf-life of the product torage	
see other section		

4.18 Use description

Use 18 - Against wood discolouring fungi

Product type	PT08 - Wood preservatives (Preservatives)
Where relevant, an exact description of the authorised use	Not available
Target organism(s) (including development stage)	Scientific name: Common name: wood discolouring fungi Development stage: Not available
Field(s) of use	Indoor Outdoor
Application method(s)	Method: Open system: brush treatment Detailed description: Not available
Application rate(s) and frequencies	Application Rate: 200-250 ml/m2 Dilution (%): 0 Number and timing of application: 200-250 g/m2
Category(ies) of users	Professional General public (non-professional)
Pack sizes and packaging material	can, not available , 1 1-20L

4.18.1 Use-specific instructions for use

see other section

4.18.2 Use-specific risk mitigation measures

see other section		
-	use, the particulars of likely direct or indirect effects, first aid measures to protect the environment	
see other section		
4.18.4 Where specific to the packaging	use, the instructions for safe disposal of the product and its	
see other section		
4.18.5 Where specific to the ເ under normal conditions of s	use, the conditions of storage and shelf-life of the product torage	
see other section		
4.19 Use description Use 19 - Against wood discolou		
Product type	PT08 - Wood preservatives (Preservatives)	
Where relevant, an exact description of the authorised use	Not available	
Target organism(s) (including development stage)	Scientific name: Common name: wood discolouring fungi Development stage: Not available	
Field(s) of use	Indoor Outdoor	
Application method(s)	Method: Open system: brush treatment Detailed description: Not available	
Application rate(s) and frequencies	Application Rate: 200-250 ml/m2 Dilution (%): 0 Number and timing of application: 200-250 g/m2	

Category(ies) of users	Professional
	General public (non-professional)
Pack sizes and packaging material	can, not available , 1
	1-20L
4.19.1 Use-specific instruct	ions for use
see other section	
4.19.2 Use-specific risk miti	gation measures
see other section	
-	e use, the particulars of likely direct or indirect effects, first aid y measures to protect the environment
see other section	
4.19.4 Where specific to the packaging	e use, the instructions for safe disposal of the product and its
see other section	
1.19.5 Where specific to the under normal conditions of	use, the conditions of storage and shelf-life of the product storage
see other section	
4.20 Use description	
Use 20 - Against wood discold	puring fungi
Product type	PT08 - Wood preservatives (Preservatives)

Where relevant, an exact description of the authorised	Not available	
use Target organism(s) (including development stage)	Scientific name: Common name: wood discolouring fungi Development stage: Not available	
Field(s) of use	Indoor Outdoor	
Application method(s)	Method: Open system: brush treatment Detailed description: Not available	
Application rate(s) and frequencies	Application Rate: 200-250 ml/m2 Dilution (%): 0 Number and timing of application: 200-250 g/m2	
Category(ies) of users	Professional General public (non-professional)	
Pack sizes and packaging material	can, not available , 1 1-20L	
4.20.1 Use-specific instructions for use		
see other section		
4.20.2 Use-specific risk mitigation measures		
see other section		

4.20.3 Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

see other section		
4.20.4 Where specific to the use, the instructions for safe disposal of the product and its packaging		
see other section		
4.20.5 Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage		
see other section		
4.21 Use description		
Use 21 - Against wood discolouring fungi		
Product type	PT08 - Wood preservatives (Preservatives)	
Where relevant, an exact description of the authorised use	Not available	
Target organism(s) (including development stage)	Scientific name: Common name: wood discolouring fungi Development stage: Not available	
Field(s) of use	Indoor Outdoor	
Application method(s)	Method: Open system: brush treatment Detailed description: Not available	
Application rate(s) and frequencies	Application Rate: 200-250 ml/m2 Dilution (%): 0 Number and timing of application: 200-250 g/m2	
Category(ies) of users	Professional General public (non-professional)	

can, not available , 1

Pack sizes and packaging material

4.21.1 Use-specific instructions for use
see other section
4.21.2 Use-specific risk mitigation measures
see other section
4.21.3 Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment
see other section
4.21.4 Where specific to the use, the instructions for safe disposal of the product and its packaging
see other section
4.21.5 Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage
see other section

1-20L

- 5. General directions for use
- 5.1. Instructions for use

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and outer parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Hazel)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Boxwood)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Blue)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Ebony)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Teak)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Dark Oak)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Pine)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Oregon)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Colourless)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Olive Green)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Cedar)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Fir green)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Mahogany)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Chestnut)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Light Oak)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Old Pine)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Larch)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Rosewood)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Russian Green)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

5.2. Risk mitigation measures

Sikkens Cetol HLS plus(BP) Keep out of reach of children. Wear suitable protective clothing and gloves. Sikkens Cetol HLS plus (BP) (Hazel) Keep out of reach of children. Wear suitable protective clothing and gloves. Sikkens Cetol HLS plus (BP) (Boxwood) Keep out of reach of children. Wear suitable protective clothing and gloves. Sikkens Cetol HLS plus (BP) (Blue) Keep out of reach of children. Wear suitable protective clothing and gloves. Sikkens Cetol HLS plus (BP) (Ebony) Keep out of reach of children. Wear suitable protective clothing and gloves. Sikkens Cetol HLS plus (BP) (Teak) Keep out of reach of children. Wear suitable protective clothing and gloves. Sikkens Cetol HLS plus (BP) Keep out of reach of children. Wear suitable protective clothing and gloves. Sikkens Cetol HLS plus (BP) (Dark Oak) Keep out of reach of children. Wear suitable protective clothing and gloves. Sikkens Cetol HLS plus (BP) (Pine) Keep out of reach of children. Wear suitable protective clothing and gloves. Sikkens Cetol HLS plus (BP) (Oregon) Keep out of reach of children. Wear suitable protective clothing and gloves. Sikkens Cetol HLS plus (BP) (Colourless) Keep out of reach of children. Wear suitable protective clothing and gloves. Sikkens Cetol HLS plus (BP) (Olive Green) Keep out of reach of children. Wear suitable protective clothing and gloves. Sikkens Cetol HLS plus (BP) (Cedar) Keep out of reach of children. Wear suitable protective clothing and gloves. Sikkens Cetol HLS plus (BP) (Fir green) Keep out of reach of children. Wear suitable protective clothing and gloves. Sikkens Cetol HLS plus (BP) (Mahogany) Keep out of reach of children. Wear suitable protective clothing and gloves. Sikkens Cetol HLS plus (BP) (Chestnut) Keep out of reach of children. Wear suitable protective clothing and gloves. Sikkens Cetol HLS plus (BP) (Light Oak) Keep out of reach of children. Wear suitable protective clothing and gloves. Sikkens Cetol HLS plus (BP) (Old Pine)

5.3. Particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

Keep out of reach of children. Wear suitable protective clothing and gloves.

Keep out of reach of children. Wear suitable protective clothing and gloves.

Keep out of reach of children. Wear suitable protective clothing and gloves.

Keep out of reach of children. Wear suitable protective clothing and gloves

Sikkens Cetol HLS plus (BP) (Larch)

Sikkens Cetol HLS plus (BP) (Rosewood)

Sikkens Cetol HLS plus (BP) (Russian Green)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur.

If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs.

After inhalation: Move affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Hazel)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Boxwood)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Blue)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Ebony)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Teak)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Dark Oak)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce

vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Pine)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Oregon)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Colourless)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately. Sikkens Cetol HLS plus (BP) (Olive Green)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Cedar)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Fir green)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Mahogany)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Chestnut)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Light Oak)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Old Pine)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Larch)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Rosewood)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Russian Green)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

5.4. Instructions for safe disposal of the product and its packaging

European waste code (EWC): 03 02 05: other wood preservatives containing dangerous substances / 20 01 27: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Hazel)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Boxwood)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Blue)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Ebony)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Teak)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Dark Oak)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Pine)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Oregon)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Colourless)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Olive Green)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Cedar)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Fir green)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Mahogany)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Chestnut)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Light Oak)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Old Pine)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Larch)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Rosewood)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Russian Green)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

5.5. Conditions of storage and shelf-life of the product under normal conditions of storage

Store product in tightly closed original containers at temperatures about 5 - 30°C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Hazel)

Store product in tightly closed original containers at temperatures about $5-30^{\circ}$ C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Boxwood)

Store product in tightly closed original containers at temperatures about $5-30^{\circ}$ C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Blue)

Store product in tightly closed original containers at temperatures about $5-30^{\circ}$ C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Ebony)

Store product in tightly closed original containers at temperatures about $5-30^{\circ}$ C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Teak)

Store product in tightly closed original containers at temperatures about $5-30^{\circ}$ C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP)

Store product in tightly closed original containers at temperatures about $5-30^{\circ}$ C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Dark Oak)

Store product in tightly closed original containers at temperatures about $5-30^{\circ}$ C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Pine)

Store product in tightly closed original containers at temperatures about $5-30^{\circ}$ C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Oregon)

Store product in tightly closed original containers at temperatures about 5-30 °C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Colourless)

Store product in tightly closed original containers at temperatures about $5-30^{\circ}$ C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Olive Green)

Store product in tightly closed original containers at temperatures about $5-30^{\circ}$ C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Cedar)

Store product in tightly closed original containers at temperatures about 5-30 °C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Fir green)

Store product in tightly closed original containers at temperatures about $5-30^{\circ}$ C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Mahogany)

Store product in tightly closed original containers at temperatures about $5-30^{\circ}$ C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Chestnut)

Store product in tightly closed original containers at temperatures about $5-30^{\circ}$ C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Light Oak)

Store product in tightly closed original containers at temperatures about $5-30^{\circ}$ C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Old Pine)

Store product in tightly closed original containers at temperatures about 5-30 °C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Larch)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room

temperature.

Sikkens Cetol HLS plus (BP) (Rosewood)

Store product in tightly closed original containers at temperatures about $5-30^{\circ}$ C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Russian Green)

Store product in tightly closed original containers at temperatures about $5-30^{\circ}$ C. The product is stable for 3 years at room temperature.

6. Other information

Sikkens Cetol HLS plus(BP), DK

Sikkens Cetol HLS plus(BPR), IT

Sikkens Cetol HLS plus(BPR), CH

Xyladecor Holzschutzlasur BPR. AT

Xyladecor Classic HP(BPR), CZ

Xyladecor Classic HP(BPR), SK

Vivexyl Plus, GR

SADOLIN Classic HP(BPR), HU

SADOLIN Classic HP(BPR), PL

SADOLIN IMPREGNAT CLASSIC HP(BPR), PL

SADOLIN Classic(BPR), PL

SADOLIN IMPREGNAT CLASSIC(BPR), PL

Vivexyl Plus, CY

Vivexyl Plus, BG

Sikkens Cetol HLS plus(BP)

Use biocides safely. Always read the label and product information before use.

P501: Dispose of container to local rules

Sikkens Cetol HLS plus (BP) (Hazel)

Use biocides safely. Always read the label and product information before use.

Suplementary statemet under Labelling: "Contains 3-iodo-2-propynyl butylcarbamate and 2-butanone oxime."

Sikkens Cetol HLS plus (BP) (Boxwood)

Use biocides safely. Always read the label and product information before use.

Suplementary statemet under Labelling: "Contains 3-iodo-2-propynyl butylcarbamate and 2-butanone oxime."

Sikkens Cetol HLS plus (BP) (Blue)

Use biocides safely. Always read the label and product information before use.

Suplementary statemet under Labelling: "Contains 3-iodo-2-propynyl butylcarbamate and 2-butanone oxime."

Sikkens Cetol HLS plus (BP) (Ebony)

Use biocides safely. Always read the label and product information before use.

Suplementary statemet under Labelling: "Contains 3-iodo-2-propynyl butylcarbamate and 2-butanone oxime."

Sikkens Cetol HLS plus (BP) (Teak)

Use biocides safely. Always read the label and product information before use.

Suplementary statemet under Labelling: "Contains 3-iodo-2-propynyl butylcarbamate and 2-butanone oxime."

Sikkens Cetol HLS plus (BP)

Use biocides safely. Always read the label and product information before use.

Suplementary statemet under Labelling: "Contains 3-iodo-2-propynyl butylcarbamate and 2-butanone oxime."

Sikkens Cetol HLS plus (BP) (Dark Oak)

Use biocides safely. Always read the label and product information before use.

Suplementary statemet under Labelling: "Contains 3-iodo-2-propynyl butylcarbamate and 2-butanone oxime."

Sikkens Cetol HLS plus (BP) (Pine)

Use biocides safely. Always read the label and product information before use.

Suplementary statemet under Labelling: "Contains 3-iodo-2-propynyl butylcarbamate and 2-butanone oxime."

Sikkens Cetol HLS plus (BP) (Oregon)

Use biocides safely. Always read the label and product information before use.

Suplementary statemet under Labelling: "Contains 3-iodo-2-propynyl butylcarbamate and 2-butanone oxime."

Sikkens Cetol HLS plus (BP) (Colourless)

Use biocides safely. Always read the label and product information before use.

Suplementary statemet under Labelling: "Contains 3-iodo-2-propynyl butylcarbamate and 2-butanone oxime."

Sikkens Cetol HLS plus (BP) (Olive Green)

Use biocides safely. Always read the label and product information before use.

Suplementary statemet under Labelling: "Contains 3-iodo-2-propynyl butylcarbamate and 2-butanone oxime."

Sikkens Cetol HLS plus (BP) (Cedar)

Use biocides safely. Always read the label and product information before use.

Suplementary statemet under Labelling: "Contains 3-iodo-2-propynyl butylcarbamate and 2-butanone oxime."

Sikkens Cetol HLS plus (BP) (Fir green)

Use biocides safely. Always read the label and product information before use.

Suplementary statemet under Labelling: "Contains 3-iodo-2-propynyl butylcarbamate and 2-butanone oxime."

Sikkens Cetol HLS plus (BP) (Mahogany)

Use biocides safely. Always read the label and product information before use.

Suplementary statemet under Labelling: "Contains 3-iodo-2-propynyl butylcarbamate and 2-butanone oxime."

Sikkens Cetol HLS plus (BP) (Chestnut)

Use biocides safely. Always read the label and product information before use.

Suplementary statemet under Labelling: "Contains 3-iodo-2-propynyl butylcarbamate and 2-butanone oxime."

Sikkens Cetol HLS plus (BP) (Light Oak)

Use biocides safely. Always read the label and product information before use.

Suplementary statemet under Labelling: "Contains 3-iodo-2-propynyl butylcarbamate and 2-butanone oxime."

Sikkens Cetol HLS plus (BP) (Old Pine)

Use biocides safely. Always read the label and product information before use.

Suplementary statemet under Labelling: "Contains 3-iodo-2-propynyl butylcarbamate and 2-butanone oxime."

Sikkens Cetol HLS plus (BP) (Larch)

Use biocides safely. Always read the label and product information before use.

Suplementary statemet under Labelling: "Contains 3-iodo-2-propynyl butylcarbamate and 2-butanone oxime."

Sikkens Cetol HLS plus (BP) (Rosewood)

Use biocides safely. Always read the label and product information before use.

Suplementary statemet under Labelling: "Contains 3-iodo-2-propynyl butylcarbamate and 2-butanone oxime."

Sikkens Cetol HLS plus (BP) (Russian Green)

Use biocides safely. Always read the label and product information before use.

Suplementary statemet under Labelling: "Contains 3-iodo-2-propynyl butylcarbamate and 2-butanone oxime."

Bilag 1

Oplysninger til etiket og brugsanvisning for Sikkens Cetol HLS Plus (BP), BPR-reg. nr. 782-7

Rettelse: Tilføjet H412 til bilag 1.

- I. Etiketten skal udformes i overensstemmelse med artikel 69 i biocidforordningen (Forordning (EU) nr. 528/2012), og CLP Forordningen1.
- II. Det er udelukkende ansøgers/godkendelsesindehaverens ansvar, at etiket, mærkning og pakning lever op til lovens krav, jf. biocidforordningen artikel 69. Nedstående tekst i afsnit III er bidrag til overholdelsen af reglerne og således kun en del af de krav, som stilles til blandt andet etiketten.
- III. Etiketten skal indeholde nedenstående oplysninger. Oplysninger i citationstegn skal angives ordret:
- 1) I hovedfeltet:
- "Træbeskyttelsesmiddel (PT8)

Må kun anvendes over jord som træbeskyttelse mod blåsplint. Må kun anvendes i brugsklasse 2 og 3 jf. DS/EN335-1."

- 2) I advarselsfeltet:
- " FORSIGTIG

Skadelig for vandlevendeorganismer, medlangvarige virkninger (H412)

Undgå udledning til miljøet (P273)

Vær opmærksom på, at Arbejdstilsynet har regler for arbejde med bekæmpelsesmidler. Læs nærmere i det eventuelt lovpligtige sikkerhedsdatablad samt i Arbejdstilsynets informationsmateriale om bekæmpelsesmidler.

Vask huden efter arbeide.

1 Europa-Parlamentets og Rådets forordning (EF) Nr. 1272/2008 af 16. december 2008

om klassificering, mærkning og emballering af stoffer og blandinger og om ændring og ophævelse af direktiv 67/548/EØF og 1999/45/EF og om ændring af forordning (EF) nr. 1907/2006

Overtrædelse af nedenstående særligt fremhævede forskrifter kan medføre straf:

Må kun anvendes over jord som træbeskyttelse mod blåsplint. Må kun anvendes i brugsklasse 2 og 3 jf. DS/EN335-1.

Må kun anvendes i doseringer på 200-250 ml/m2 ved pensling.

Må ikke anvendes mod andre skadevoldere og ikke i højere doseringer end de i brugsanvisningen nævnte.

Må ikke anvendes indendørs.

Må ikke anvendes til træværk, der kommer i direkte berøring med fødevarer og foderstoffer.

Opbevares utilgængeligt for børn.

Må ikke opbevares sammen med fødevarer, drikkevarer og foderstoffer.

Evt. oplysninger om førstehjælp.

- 3) I deklarationsfeltet:
- a) Teksten "Træbeskyttelsesmiddel BPR-reg. nr. 782-7. Aktivstof og biocidholdigt produkt er godkendt efter biocidforordningen (Forordning (EU) nr. 528/2012)".
- b) Oplysning om præparattype: "væske" for dette præparat.
- c) Indholdet af aktivstof i vægtprocent og g/L ved 20 °C
- d) Sætningen: "Indeholder IPBC og 2-butanonoxim. Kan udløse allergisk reaktion"
- e) Udløbsdatoen skal anføres. Denne dato må højst være 3 år efter produktionsdatoen. Etikettens dato kan udformes som en henvisning til en produktionsdato andetsteds på emballagen.
- f) Batchnummer eller betegnelse skal anføres.
- g) Pakningsstørrelse i liter.
- h) Navn og firmaadresse, herunder telefonnummer, for en i en medlemsstat etableret fysisk eller juridisk person, som er ansvarlig for markedsføringen (godkendelsesindehaveren).
- 4) Brugsanvisningen:

Oplysninger om skadevoldere, anvendelsesområde og doseringer.

Følgende retningslinjer gælder i forhold til bortskaffelse.

Der skal mærkes med sikkerhedssætning P501: "Indholdet/beholderen bortskaffes i overensstemmelse med kommunale regler for affaldshåndtering."

Derudover skal mærkningen ske efter følgende retningslinjer:

Tom emballage og rester bortskaffes i henhold til kommunale retningslinjer.